



Fall Protection: Rope Grabs

Explain dangers

With rope grabs, there are three basic hazards:

1. Attaching them the wrong way
2. Grabbing hold of the device or the rope above it during a fall
3. Using them with the wrong size or type of rope.

A rope grab attached upside down on a lifeline will not work properly. Instead of locking on the line, it will simply slide down.

Never grab the device or the rope above it if you fall. This can prevent the rope grab from working properly. Instead of stopping, you'll slide to injury or death below.

Identify controls

Rope grabs are known as fall arresters and must meet the requirements found in CSA-Z259.2.5: Fall Arresters and Vertical Lifelines.

Fall arresters are classified and labelled as follows:

1. Automatic fall arresters – These can move freely along the lifeline according to the position of a worker. They lock automatically if you fall.
2. Manual fall arresters – These are always locked in position and require action by the worker to move it along the lifeline.

REMEMBER

When used with a rope grab, the length of a lanyard in a fall arrest system must not exceed 76 cm (30 in).

Demonstrate

Using a rope grab and lifeline, demonstrate the following as you talk:

- When attaching a rope grab to a lifeline, always make sure the arrow on the device points along the lifeline towards the anchor point (pictured).
- After putting the rope grab on the lifeline, give it a firm tug in the direction of a fall to make sure it engages.
- Some rope grabs have a "parking feature" that locks at a point on the lifeline that won't let you reach a fall hazard.
- Ensure that the lifeline and rope grab match. Rope grabs are designed to work with certain types and sizes (in diameters) of lifelines. Specifications are usually listed in the manufacturer's instructions or on the housing of the rope grab.
- A vertical lifeline must extend to the ground or have a positive stop to prevent the rope grab from running off the end of the lifeline. **REMEMBER:** Only one person at a time may use a vertical lifeline.
- Position the rope grab on a vertical lifeline as high as possible above your D-ring to minimize free fall distance.
- Make sure you have enough clearance below. Rope grabs may slide down the lifeline as much as 1 m (3.3 ft) before arresting a fall. With your crew, inspect the components of a fall arrest system used on your site.



Materials adapted with permission from Infrastructure Health and Safety Association